ternational Journal of Clothing Science and Technology 2003; 15: 16 – 27.

- Rudolf A, Geršak J. Influence of Sewing Speed on the Changes of Mechanical Properties of Differently Twisted and Lubricated Threads During The Process of Sewing. *Tekstil* 2007; 56, 5: 271 – 277.
- Pogorelova M, Kamilatova O. The Influence of Deformation Pecularities of Sewing Threads on Seam Properties. *Tekhnologiya Tekstil'noy Promyshlennosti (Technology of Textile Industry)*, State Technological University of Kostroma, 2007; 304, 6: 19 – 22 (In Russian).
- Midha VK, Kothari VK, Chatopadhyay R, Mukhopadhyay A. Studies on the Changes in Tensile Properties of Sewing Thread at Different Sewing Stages. *Textile Research Journal* 2009; 79 (13): 1155 – 1167.
- Jucienė M, Vobolis J. Correlation between the Seam Stitch Length of the Sewing Garment and Friction Forces. *Material Science (Medžiagotyra)* 2007; 13, 14: 74 – 78.
- Jucienė M, Vobolis J. Investigation of the influence of defects of sewing machine V-belt drive on the stitch length. *Tekstil* 2004; 53, 5: 219 – 225.
- Jucienė M, Vobolis J. Dependence of Stitch Length along the Seam on External Friction Force Theoretical Anglysis. *Materials Science (Medžiagotyra)* 2009; 15, 3: 273 – 276.
- Vobolis J, Jucienė M, Punys J, Vaitkevičius V. Influence of Selected Machine and Material Parameters on the Stitch Length and Its Irregularity. *Fibers* & *Textiles in Eastern Europe* 2003; 11, 3 (42): 50 – 55.
- Dobilaité V, Juciené M. Influence of Sewing Machine Parameters on Seam Pucker. *Tekstil* 2007; 56, 5: 286 – 292.
- Dobilaité V, Juciené M. Seam pucker Indicators and Their Dependence upon the Parameters of sewing machine. *International Journal of Clothing Science and Technology* 2008; 20, 4: 231 – 239.
- Chernenko DA. Systematization of design parameters for automated embroidery and modeling of deformation system of "fabric-embroidery". Doctoral Disertation, State Technological University of Orel, Orel, 2006, p. 132.
- Radavičienė S, Jucienė M. Investigation of Mechanical Properties of Embroidery threads. In: 5th International Textile, Clothing & Design Conference, Dubrovnik, Croatija, 3 - 6 October 2010, pp. 494 – 499.
- El Gholmy S, Bondok N, El Geiheini A. Optimization of embroidery design on denim fabrics. In: 5th International Textile, Clothing & Design Conference, Dubrovnik, Croatija, 3 - 6 October 2010, pp. 821 – 826.

Received 25.02.2011 Reviewed 05.10.2011



LABORATORY OF BIODEGRADATION

The Laboratory of Biodegradation operates within the structure of the Institute of Biopolymers and Chemical Fibres. It is a modern laboratory with a certificate of accreditation according to Standard PN-EN/ISO/IEC-17025: 2005 (a quality system) bestowed by the Polish Accreditation Centre (PCA). The laboratory works at a global level and can cooperate with many institutions that produce, process and investigate polymeric materials. Thanks to its modern equipment, the Laboratory of Biodegradation can maintain cooperation with Polish and foreign research centers as well as manufacturers and be helpful in assessing the biodegradability of polymeric materials and textiles.

The Laboratory of Biodegradation assesses the susceptibility of polymeric and textile materials to biological degradation caused by microorganisms occurring in the natural environment (soil, compost and water medium). The testing of biodegradation is carried out in oxygen using innovative methods like respirometric testing with the



continuous reading of the CO₂ delivered. The laboratory's modern MICRO-OXYMAX RESPIROMETER is used for carrying out tests in accordance with International Standards.

The methodology of biodegradability testing has been prepared on the basis of the following standards:

- testing in aqueous medium: 'Determination of the ultimate aerobic biodegrability of plastic materials and textiles in an aqueous medium. A method of analysing the carbon dioxide evolved' (PN-EN ISO 14 852: 2007, and PN-EN ISO 8192: 2007)
- testing in compost medium: 'Determination of the degree of disintergation of plastic materials and textiles under simulated composting conditions in a laboratory-scale test. A method of determining the weight loss' (PN-EN ISO 20 200: 2007, PN-EN ISO 14 045: 2005, and PN-EN ISO 14 806: 2010)
- testing in soil medium: 'Determination of the degree of disintergation of plastic materials and textiles under simulated soil conditions in a laboratory-scale test. A method of determining the weight loss" (PN-EN ISO 11 266:



1997, PN-EN ISO 11 721-1: 2002, and PN-EN ISO 11 721-2: 2002).

The following methods are applied in the assessment of biodegradation: gel chromatography (GPC), infrared spectroscopy (IR), thermogravimet-

ric analysis (TGA) and scanning electron microscopy (SEM).

Contact:

INSTITUTE OF BIOPOLYMERS AND CHEMICAL FIBRES ul. M. Skłodowskiej-Curie 19/27, 90-570 Łódź, Poland Agnieszka Gutowska Ph. D., tel. (+48 42) 638 03 31, e-mail: lab@ibwch.lodz.pl